



OmniAire 1000V

Omnitec Design, Manufacturing Air Purification Equipment Since 1988

Air scrubber for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. Accessories include HEPA filter, activated carbon filters and germicidal UV-C light for removal of asbestos, lead, chemical fumes and biological contaminants. Provides cleaner and healthier environment at construction/renovation projects and industrial facilities.

OmniAire 1000V

SPECIFICATIONS


Net Weight With Filters	75 lbs.
Dimensions (LxWxH)	32"x18"x21"
Operating Speeds	Variable
Airflow Ratings (cfm)*	300 to 950
Filtration Stages	3 to 5
HEPA Filter 99.97%, 0.3µ	Yes
Cabinetry	Aluminum, silicone sealed before riveting
Exhaust Collar Diameter	10"
Carrying Handles w/Rubber Grips	2
3" Casters	4 Swivel
Motor With Thermal Overload	1/2 hp
Circuit Requirements (Volts/Hz)	115V/60Hz
Maximum Operating Amps	5.8 amps
Pressure Gauge	0-3" W.C.

*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.




ORDERING INFO.....PART

OmniAire 1000V.....	OA1000V
HEPA Filter 99.97%, 0.3µ	OAH1616
Primary/Secondary Filter (qty 20)	OAP1818
Intake Manifold, 10"	OAIM10
Quick Clamp, 8 to 10"	QCW12
Flexible Duct, 10" x 25'	OAD10
OdorGuard 600 Carbon Filter	OG1616
UVGI Germicidal Light Module	UVCM1000
UV-C Emitter Tube, 10½" J	EUV105JD



OmniAire 1000V comes standard with a particle board 99.97% 0.3µ HEPA filter and can be upgraded to a metal frame Certified 99.99% 0.3µ HEPA.



Optional Accessories



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

3067108

www.omnitedesign.com

2125 196th Street SW, Suite 115, Lynnwood, WA 98036

phone 425-774-3257 fax 425-774-4983