

OMNITEC *OmniAire 1200PAC/FR* DESIGN, INC. Omnitec Design, Manufacturing Air Purification Equipment Since 1988

The **OmniAire Portable Air Cleaner (PAC)** machine with 99.99% HEPA and UVGI germicidal lights eliminates sub-micron particulates and microbial contamination. Designed for healthcare environments, it offers quiet operation as the air is exhausted through the HEPA filter. This unit has fully adjustable air flow and a small footprint.

OmniAire 1200 PAC/FR is used for:

**Air Purification and Sterilization in Healthcare
Veterinary Clinics
Hospital Pharmacies - USP 797 Requirements
First Response Shelters, Mobile Hospitals
Laboratories, Clean Rooms
Isolation Rooms - Positive or Negative Room
Pressurization
Morgues & Mortuaries
Archives**



OmniAire 1200 PAC/FR Specifications:

Air flow: 200 to 1100 cfm with variable speed control
Filtration: Primary Filter - 40% Pleated Filter
 HEPA Filter - 99.99%, .3μ, metal frame, 16"x16"x12", individually tested and Certified
Power: 115 Volts, 60 Hz, 6 amp maximum
Controls: Recessed panel with Variable Speed Control
 Differential pressure indicator, 0-3" WC to indicate HEPA filter loading;
 Hour meter with LCD display;
 UVGI lights ON/OFF switch and lamps/ballast status LED lights;
Construction: Aluminum Housing with Galvanized Metal reinforcements, riveted and silicone sealed
Size: 19" x 22" x 42" high with 3" casters
Weight: 105 lbs.
Connections: Inlet with 16"x16" pleated filter and protective screen. Discharge on top through HEPA and protective screen

ORDERING INFO	PART #
OmniAire 1200PAC/FR.....	OA1200PAC/FR
HEPA Filter 99.99%, 0.3μ	OAH1616G
Primary Pleated Filter.....	OFP16
Connection Adapter, 10"	OAIM10
Quick Clamp, 8 to 10"	QCW12
Flexible Duct, 10" x 25'.....	OAD10
OdorGuard 600 Carbon Filter	OG1616
UV-C Emitter Tube, 10½" J.....	EUV105JD

Optional accessories:

Connection adapter for 10" diameter flex hose on the discharge and/or suction side
 OdorGuard 600 high capacity carbon fiber filter
 OdorGuard 750 high capacity carbon/alumina fiber filter



Optional Accessories

Note:

- OmniAire 1200 PAC/FR can be ordered to operate on 230 VAC/60-50 Hz
- Also available in a 99.99% @ .1-.2μ HEPA Filter



3067108

CONFORMS TO UL STD 507
 CERTIFIED TO CAN/CSA STD
 C22.2 NO. 113-M1984

www.omnitecdesign.com
 2125 196th Street SW, Suite 115, Lynnwood, WA 98036
 phone 425-774-3257 fax 425-774-4983