



OmniAire 1200PAC

Omnitec Design, Manufacturing Air Purification
Equipment Since 1988

The **OmniAire Portable Air Cleaner (PAC)** machine with 99.99% HEPA and UVGI germicidal lights eliminates sub-micron particulates and microbial contamination. Designed for healthcare environments, it offers quiet operation as the air is exhausted through the HEPA filter. This unit has fully adjustable air flow and a small footprint.

OmniAire 1200 PAC is used for:

- Air Purification and Sterilization in Healthcare
- Veterinary Clinics
- Hospital Pharmacies - USP 797 Requirements
- First Response Shelters, Mobile Hospitals
- Laboratories, Clean Rooms
- Isolation Rooms - Positive or Negative Room Pressurization
- Morgues & Mortuaries
- Archives



OmniAire 1200 PAC Specifications:

- Air flow:** 200 to 1100 cfm with variable speed control
- Filtration:** Primary Filter - 40% Pleated Filter
HEPA Filter - 99.99%, .3μ, metal frame, 16"x16"x12", individually tested and Certified
- Power:** 115 Volts, 60 Hz, 6 amp maximum
- Controls:** Recessed panel with Variable Speed Control
Differential pressure indicator, 0-3" WC to indicate HEPA filter loading;
Hour meter with LCD display;
UVGI lights ON/OFF switch and lamps/ballast status LED lights;
- Construction:** Aluminum Housing with Galvanized Metal reinforcements, riveted and silicone sealed
- Size:** 19" x 22" x 42" high with 3" casters
- Weight:** 105 lbs.
- Connections:** Inlet with 16"x16" pleated filter and protective screen. Discharge on top through HEPA and protective screen

ORDERING INFO	PART #
OmniAire 1200PAC	OA1200PAC
HEPA Filter 99.99%, 0.3μ	OAH1616G
Primary Pleated Filter	OFP16
Connection Adapter, 10"	OAIM10
Quick Clamp, 8 to 10"	QCW12
Flexible Duct, 10" x 25'	OAD10
OdorGuard 600 Carbon Filter	OG1616
UV-C Emitter Tube, 10½" J	EUV105JD

Optional accessories:

- Connection adapter for 10" diameter flex hose on the discharge and/or suction side
- OdorGuard 600 high capacity carbon fiber filter
- OdorGuard 750 high capacity carbon/alumina fiber filter

Note:

- OmniAire 1200 PAC can be ordered to operate on 230 VAC/60-50 Hz
- Also available in a 99.99% @ .1-.2μ HEPA Filter



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

3067108

www.omnitecdesign.com
2125 196th Street SW, Suite 115, Lynnwood, WA 98036
phone 425-774-3257 fax 425-774-4983