



# OmniAire 2200

Omnitec Design, Manufacturing Air Purification Equipment Since 1988

Air scrubber for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. Accessories include HEPA filter and activated carbon filters for removal of asbestos, lead, chemical fumes and biological contaminants. Provides cleaner and healthier environment at construction/renovation projects and industrial facilities.

## OmniAire 2200

### SPECIFICATIONS

<b>Net Weight With Filters</b> .....	125 lbs.
<b>Dimensions (LxWxH)</b> .....	34"x26"x31"
<b>Operating Speeds</b> .....	2 Speed
<b>Airflow Ratings (cfm)*</b> .....	1000, 2000
<b>Filtration Stages</b> .....	3 to 5
<b>HEPA Filter 99.97%, 0.3µ</b> .....	Yes
<b>Cabinetry</b> .....	Aluminum/Galvanized Steel/Epoxy Paint
<b>Closed End Rivet Construction</b> .....	Yes
<b>Silicon Sealed Seams Before Riveting</b> .....	Yes
<b>Exhaust Collar Diameter</b> .....	12"
<b>Carrying Handles w/Rubber Grips</b> .....	2
<b>5" Casters, 2 Fixed, 2 Swivel</b> .....	Yes
<b>Reinforced Caster Mounting Channels</b> .....	Yes
<b>Recessed Controls</b> .....	Yes
<b>Motor Horse Power</b> .....	1 hp
<b>Circuit Requirements (Volts/Hz)</b> .....	115V/60Hz
<b>Maximum Operating Amps</b> .....	12.0 amps
<b>Thermal Overload Protection</b> .....	Yes
<b>Pressure Gauge</b> .....	0-5" W.C.

\*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



### ORDERING INFO.....PART #

OmniAire 2200.....	OA2200
HEPA Filter 99.97%, 0.3µ .....	OAH2424
Primary/Secondary Filter (qty 20) .	OAP2424
Intake Manifold, 14" .....	OAIM2200
Quick Clamp, 12".....	QC12
Flexible Duct, 12"x25' .....	OAD12
Quick Clamp, 14".....	QC14
Flexible Duct, 14"x25' .....	OFD14
Carbon Vapor Trap Filter .....	OCVT2424
OdorGuard 600 Carbon Filter .....	OG2424
OdorGuard 750 Plus Carbon Filter	OGP2424



Optional Accessories



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

3067108

[www.omnitecdesign.com](http://www.omnitecdesign.com)

2125 196th Street SW, Suite 115, Lynnwood, WA 98036

phone 425-774-3257 fax 425-774-4983