



OmniAire 2200

Omnitec Design, Manufacturing Air Purification Equipment Since 1988

Air scrubber for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. Accessories include HEPA filter and activated carbon filters for removal of asbestos, lead, chemical fumes and biological contaminants. Provides cleaner and healthier environment at construction/renovation projects and industrial facilities.

OmniAire 2200

SPECIFICATIONS

Net Weight With Filters	125 lbs.
Dimensions (LxWxH)	34"x26"x31"
Operating Speeds	2 Speed
Airflow Ratings (cfm)*	1000, 2000
Filtration Stages	3 to 5
HEPA Filter 99.97%, 0.3µ	Yes
Cabinetry	Aluminum/Galvanized Steel/Epoxy Paint
Silicone Sealed Seams Before Riveting	Yes
Exhaust Collar Diameter	12"
Carrying Handles w/Rubber Grips	2
5" Casters, 2 Fixed, 2 Swivel	Yes
Reinforced Caster Mounting Channels	Yes
Recessed Controls	Yes
Motor With Thermal Overload	1½ hp
Circuit Requirements (Volts/Hz)	115V/60Hz
Maximum Operating Amps	13.8 amps
Pressure Gauge	0-5" W.C.

*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



ORDERING INFO.....PART

OmniAire 2200	OA2200
HEPA Filter 99.97%, 0.3µ	OAH2424
Primary/Secondary Filter (qty 20)	OAP2424
Intake Manifold, 14"	OAIM2200
Flexible Duct, 12"x25'	OAD12
Quick Clamp, 12 to 14"	QCW14
Flexible Duct, 14"x25'	OFD14
Carbon Vapor Trap Filter	OCVT2424
OdorGuard 600 Carbon Filter	OG2424
Bag Filter Housing	HBF2200
Bag Filter, 95% ASHRAE.....	OBF10



Optional Accessories



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

3067108

www.omnitecdesign.com

2125 196th Street SW, Suite 115, Lynnwood, WA 98036

phone 425-774-3257 fax 425-774-4983