

Air scrubber for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. Accessories include HEPA filter, activated carbon filters and germicidal UV-C light for removal of asbestos, lead, chemical fumes and biological contaminants. Provides cleaner and healthier environment at construction/renovation projects and industrial facilities.

OmniForce II

SPECIFICATIONS

Net Weight With Filters	95 lbs.
Dimensions (LxWxH)	32"x18"x28"
Operating Speeds	Variable
Airflow Ratings (cfm)*	200 to 1900
Filtration Stages	3 to 5
HEPA Filter 99.97%, 0.3μ	Yes
Cabinetry	Aluminum, silicone sealed before riveting
Exhaust Collar Diameter	14"
Carrying Handles w/Rubber Grips	2
3" Casters	4 Swivel
Recessed Controls	Yes
Motor With Thermal Overload	1 hp
Circuit Requirements (Volts/Hz)	115V/60Hz
Maximum Operating Amps	12.0 amps
Pressure Gauge	0-5" W.C.

*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



ORDERING INFO.....PART

OmniForce II	OF100V
HEPA Filter 99.97%, 0.3μ	OFH12
Primary/Secondary Filter (qty 20)	OFF2518
Intake Manifold, 14"	OFM14
Quick Clamp, 14"	QCW14
Flexible Duct, 14"x25'	OFD14
Carbon Vapor Trap Filter	OCVT18
OdorGuard 600 Carbon Filter	OG2116



The OmniForce II is easily transported in two pieces. Use with HEPA or Carbon Vapor Trap Filter.



Optional Accessories



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

www.omnitecdesign.com

2125 196th Street SW, Suite 115, Lynnwood, WA 98036

phone 425-774-3257 fax 425-774-4983