



# OmniAire 1200PAC

Omnitec Design, Manufacturing Air Purification  
Equipment Since 1988

The **OmniAire Portable Air Cleaner (PAC)** machine with 99.99% HEPA and UVGI germicidal lights eliminates sub-micron particulates and microbial contamination. Designed for healthcare environments, it offers quiet operation as the air is exhausted through the HEPA filter. This unit has fully adjustable air flow and a small footprint.

## OmniAire 1200 PAC is used for:

- Air Purification and Sterilization in Healthcare**
- Veterinary Clinics**
- Hospital Pharmacies - USP 797 Requirements**
- First Response Shelters, Mobile Hospitals**
- Laboratories, Clean Rooms**
- Isolation Rooms - Positive or Negative Room Pressurization**
- Morgues & Mortuaries**
- Archives**



## OmniAire 1200 PAC Specifications:

- Air flow:** 200 to 1100 cfm with variable speed control
- Filtration:** Primary Filter - 40% Pleated Filter  
HEPA Filter - 99.99%, .3μ, metal frame, 16"x16"x12", individually tested and Certified
- Power:** 115 Volts, 60 Hz, 6 amp maximum
- Controls:** Recessed panel with Variable Speed Control  
Differential pressure indicator, 0-3" WC to indicate HEPA filter loading;  
Hour meter with LCD display;  
UVGI lights ON/OFF switch and lamps/ballast status LED lights;
- Construction:** Aluminum Housing with Galvanized Metal reinforcements, riveted and silicone sealed
- Size:** 19" x 22" x 42" high with 3" casters
- Weight:** 105 lbs.
- Connections:** Inlet with 16"x16" pleated filter and protective screen. Discharge on top through HEPA and protective screen

ORDERING INFO .....	PART #
OmniAire 1200PAC .....	OA1200PAC
HEPA Filter 99.99%, 0.3μ .....	OAH1616G
Primary Pleated Filter .....	OFP16
Connection Adapter, 10" .....	OAIM10
Quick Clamp, 8 to 10" .....	QCW12
Flexible Duct, 10" x 25' .....	OAD10
OdorGuard 600 Carbon Filter .....	OG1616
UV-C Emitter Tube, 10½" J .....	EUV105JD

## Optional accessories:

- Connection adapter for 10" diameter flex hose on the discharge and/or suction side
- OdorGuard 600 high capacity carbon fiber filter
- OdorGuard 750 high capacity carbon/alumina fiber filter

## Note:

- OmniAire 1200 PAC can be ordered to operate on 230 VAC/60-50 Hz
- Also available in a 99.99% @ .1-.2μ HEPA Filter



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

3067108

[www.omnitecdesign.com](http://www.omnitecdesign.com)  
2125 196th Street SW, Suite 115, Lynnwood, WA 98036  
phone 425-774-3257 fax 425-774-4983