

Air scrubber for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. Accessories include HEPA filter and activated carbon filters for removal of asbestos, lead, chemical fumes and biological contaminants. Provides cleaner and healthier environment at construction/renovation projects and industrial facilities.

## OmniAire 2200

### SPECIFICATIONS

|  |                                       |
|--|---------------------------------------|
| <b>Net Weight With Filters .....</b>               | 125 lbs.                              |
| <b>Dimensions (LxWxH) .....</b>                    | 34"x26"x31"                           |
| <b>Operating Speeds .....</b>                      | 2 Speed                               |
| <b>Airflow Ratings (cfm)* .....</b>                | 1000, 2000                            |
| <b>Filtration Stages .....</b>                     | 3 to 5                                |
| <b>HEPA Filter 99.97%, 0.3µ .....</b>              | Yes                                   |
| <b>Cabinetry.....</b>                              | Aluminum/Galvanized Steel/Epoxy Paint |
| <b>Silicone Sealed Seams Before Riveting .....</b> | Yes                                   |
| <b>Exhaust Collar Diameter .....</b>               | 12"                                   |
| <b>Carrying Handles w/Rubber Grips .....</b>       | 2                                     |
| <b>5" Casters, 2 Fixed, 2 Swivel.....</b>          | Yes                                   |
| <b>Reinforced Caster Mounting Channels .....</b>   | Yes                                   |
| <b>Recessed Controls .....</b>                     | Yes                                   |
| <b>Motor With Thermal Overload .....</b>           | 1½ hp                                 |
| <b>Circuit Requirements (Volts/Hz) .....</b>       | 115V/60Hz                             |
| <b>Maximum Operating Amps.....</b>                 | 13.8 amps                             |
| <b>Pressure Gauge .....</b>                        | 0-5" W.C.                             |

\*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



### ORDERING INFO ..... PART #

|                                      |             |
|--------------------------------------|-------------|
| OmniAire 2200 .....                  | OA2200      |
| HEPA Filter 99.97%, 0.3µ .....       | OAH2424L    |
| Primary/Secondary Filter (qty 20) .. | OAP2424     |
| Intake Manifold, 12" .....           | OAIM2200-12 |
| Flexible Duct, 12"x25' .....         | OAD12       |
| Quick Clamp, 12 to 14" .....         | QCW14       |
| Carbon Vapor Trap Filter .....       | OCVT2424    |
| OdorGuard 600 Carbon Filter.....     | OG2424      |
| Bag Filter Housing.....              | HBF2200     |
| Bag Filter, 95% ASHRAE.....          | OBF10       |



Optional Accessories



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

3067108

[www.omnitecdesign.com](http://www.omnitecdesign.com)

2125 196th Street SW, Suite 115, Lynnwood, WA 98036

phone 425-774-3257 fax 425-774-4983