



OmniAire 2200C

Omnitec Design, Manufacturing Air Purification
Equipment Since 1988

The OmniAire 2000C is a construction grade machine. It delivers the performance of full sized negative air units but is easy to move and set up. Equipped with a 99.97% HEPA filter and 2-stage prefilter, it is used on asbestos, lead and mold abatement projects. The HEPA filter can be replaced with an economical 95% ASHRAE Bag Filter to collect bulk dust from cutting and grinding of concrete, wood and plaster.

OmniAire 2200C

SPECIFICATIONS

Net Weight With Filters	145 lbs.
Dimensions (LxWxH)	34"x26"x31"
Operating Speeds	2 Speed
Airflow Ratings (cfm)*	1000, 2000
Filtration Stages	3 to 5
HEPA Filter 99.97%, 0.3µ	Yes
Cabinetry.....	Galvanized Steel
Silicone Sealed Seams Before Riveting	Yes
Exhaust Collar Diameter	12"
Carrying Handles w/Rubber Grips	2
5" Casters, 2 Fixed, 2 Swivel.....	Yes
Reinforced Caster Mounting Channels	Yes
Recessed Controls	Yes
Motor With Thermal Overload	1½ hp
Circuit Requirements (Volts/Hz)	115V/60Hz
Maximum Operating Amps.....	13.8 amps
"Filter Change" Light.....	Yes

*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



ORDERING INFO PART

OmniAire 2200C	OA2200C
HEPA Filter 99.97%, 0.3µ	OAH2424
Primary/Secondary Filter (qty 20)..	OAP2424
Intake Manifold, 12"	OAIM2200-12
Flexible Duct, 12"x25'	OAD12
Quick Clamp, 12 to 14"	QCW14
Carbon Vapor Trap Filter	OCVT2424
OdorGuard 600 Carbon Filter.....	OG2424
Bag Filter Housing.....	HBF2200
Bag Filter, 95% ASHRAE.....	OBF10

Optional Accessories



3067108

CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

www.omnitecdesign.com

2125 196th Street SW, Suite 115, Lynnwood, WA 98036

phone 425-774-3257 fax 425-774-4983